DATA SHEET

SCENICVIEW B19-5

Issue: April 2009

Business Line Wide TFT display – efficiency for the office

The Business Line display SCENICVIEW B19-5 offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and rotation

Flexible connectivity with DVI and Analog

Ready for remote inventory and administration tasks due to the DisplayView Manageability tools

Design in ergonomic grey with smart details like discretely integrated speakers

ENERGY STAR

TCO Development TCO'03 DISPLAYS www.tcodevelopment.com

Works with Windows Vista®

SPEAKER

SCENICVIEW B19-5

Special features	
	DisplayView™ IT Suite
Ergonomic stand	
Stand	4-in-1 Stand
Height adjust range	110 mm
Rotation to portrait	90°
Tilt angle	-5° / +20°
Swivel angle	90°
Picture performance	
Contrast - typical	1000:1
Response time typical	5 ms
Viewing angle (h/v)	170° / 170°
Color performance	16.7 Mio colors (Hi-FRC)
Brightness - typical	300 cd/m2
Size and resolution	
Aspect ratio	5:4
Diagonal Size	19-inch (48 cm)
Resolution (native)	1280 x 1024 pixel (recommended)
Resolution (interpolated)	1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	376 x 301 mm
Pixel Pitch	0.294 mm
Frequencies	
Horizontal	30 - 80 kHz
Vertical	55 - 75 Hz
Connectivity	
Video input	1 x DVI, 1 x D-SUB
Audio sound output	2 x 1 W
Audio signal input	3.5 mm stereo phone jack
Ease-of-use menu	
Languages	Dutch, English, French, German, Italian, Russian, Spanish, Swedish
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Color	sRGB, 6500K, 9300K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position
Audio	Mute, Volume
Information	Model name, S/N, Resolution/mode, Signal input
Setup	Input select, Language, DDC-CI, OSD-Position, OSD-Timeout, Factory recall
Power consumption (typical, w/o sound)	
Soft switch off	0.6 W
Power save mode	0.6 W
Operating with EPA settings	25 W
Operating maximum brightness	31 W
Electrical values	
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Protection class	1
Compliance	
Germany	GS
Europe	CE, Nordic Swan

Compliance	
USA/Canada	FCC Class B, cUL
Australia&New Zealand	C-Tick
Russia	GOST
South Korea	MIC
China	CCC
Saudi Arabia	SASO
Argentina	IRAM
Mexico	NOM
Global	TCO'03, ENERGY STAR® 4.1, ISO13406-2 (Pixel fault class II), IT-Eco-Declaration, RoHS, WEEE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Quality and Reliability	
MTBF (demonstrated)	70000 h

Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	412 x 62 x 350
Dimension with stand (W x D x H)	412 x 210 x 402
Weight (packed)	6.8 kg
Weight (unpacked)	5.3 kg
Weight (Monitor only)	
Operating ambient temperature	5 - 35°C

Miscellaneous	
	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock prepared

Package content	
	DVI-D Data cable 1.8m, D-SUB Data cable 1.8m , Audio cable 1.8m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet
	Data cables and audio cable detachable on display

Order code	
Order Code	S26361-K1256-V150
EAN Code	4333643452193

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:
http://ts.fujitsu.com/aboutus
Take back and Recycling information:
http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions April 2009

Published by
Fujitsu Technology Solutions
http://ts.fujitsu.com/